

PS6Si

STEREO INPUT PLANTER SPEAKER



Planter Style Indoor/Outdoor Stereo Loudspeaker

6 INCH WEATHERPROOF PLANTER LOUDSPEAKER

PS6Si

Stock Number

FG01264	Terracotta
FG01366	Weathered Concrete



Features

- Artistically crafted cabinet with shaped MicroPerf™ aluminum grilles looks natural and realistic
- 6.5" dual voice coil injection-molded TCC™ (talc, carbon, and ceramic) filled polypropylene woofer with butyl rubber surround
- Dual 1" fluid-cooled tri-laminate Teteron tweeter assembly that can be adjusted to vary the sound dispersion from 180° for open areas, to 90° for corner installations.
- Separate left and right channel inputs provide stereo sound in a single loudspeaker projecting quality stereo sound over a larger area than conventional loudspeakers
- Weatherproof design ensures performance outdoors
- Designed to accommodate live plants
- Dual 3-foot burial-rated connection cables with waterproof wire-nuts to insure trouble free connection
- Can be wired in one-speaker stereo-input mode or two-speaker stereo mode

Specifications

- Dimensions: 19 1/2" W x 19 1/2" H x 19 1/2" D
- Weight: 35 lbs. (15.9 kgs)

Lifetime Limited Warranty

PRODUCT DETAILS

Recommended Amplifier Power

10 to 100 Watts

Nominal Impedance

8 Ohm, in one-speaker stereo mode

4 Ohm, in two-speaker stereo mode

Wiring Requirements

2-conductor direct burial cable at the following sizes depending on longest length of cable required (2 per speaker in one-speaker stereo mode):

Wire Gauge	Maximum Distance
16	60 ft (18 m)
14	100 ft (30 m)
12	160 ft (50 m)

Temperature Extremes

-50° to 185° Fahrenheit

-45° to 85° Celsius