BUNN®

ITEM#

PROJECT

DATE

Twin Airpot Coffee Brewer



Model CWTF Twin APS Shown with Airpots and Gourmet Funnels
(airpots sold separately)
Dimensions: 23.5" H x 16" W x 19.7" D
(59.7cm H x 40.6cm W x 50.0cm D)

Features

Twin Airpot Coffee Brewer

- Brews 15 gallons (56.8 liters) of perfect coffee per hour.
- Brews directly into 1.9 to 3.8 liter airpots.
- Twin brew head system.
- Hot water faucet.
- Convenient airpots keep coffee hot and fresh for hours.
- Airpots are easliy transported to remote meeting rooms, breakfast bars, etc.
- Digital timer enables users to make brew cycle adjustments from the front panel.
- Pourover feature on both sides.
- SplashGard® funnel deflects hot liquids away from the hand.
- Gourmet funnel model available for heavier throw weights of coffee.

For current specification sheets and other information, go to *www.bunn.com*.

Related Products

Easy Clear® EQHP-10
Product No. : 39000.0004

Easy Clear® EQHP-10L
Product No. : 39000.0001
Dimensions:



Paper Filter Pack
Product No. : 20115.6000
Packed per case: 1,000
Dimensions: 4¼" Base x 2¾" Sidewall
10.8 cm Base x 6.98 cm Sidewall



2.2 liter Push-Button Airpot
Product No. : 28696.6000
Capacity: 74 oz. (2.2 L)

2.5 liter Push-Button Airpot
Product No. : 13041.6000
Capacity: 84 oz. (2.5 L)



2.5 liter Lever-Action Airpot
Product No. : 32125.0000
Capacity: 84 oz. (2.5 L)

3.0 liter Lever-Action Airpot
Product No. : 32130.0000
Capacity: 102 oz. (3.0 L)

3.8 liter Lever-Action Airpot
Product No. : 36725.0000
Capacity: 129 oz. (3.8 L)



Universal Airpot Racks
for push-button and lever-action airpots.Five position rack is shown # 35728.0004.
See page A3.9 for more information.



Gourmet C Funnel
Product No.: 34559.7000 (7.12 inch width)
34559.7001 (7.62 inch width)



- Universal design – handle may be moved to appropriate side
- Allows brewing with heavier throw weights of coffee.
- Paper Filter Pack
  Product No. : 20100.0000
  Packed per case: 500

Model	Agency Listing
CWTF Twin APS	

Dimensions & Specifications

CANADA


Model	Product #	Volts	Amps	Tank Htr Watts	Total Watts	Capacity per hour	Cubic ft³/m³	Weight lbs/kg	Cord Attached
CWTF Twin APS	23400.6003	120/240	26	2 @ 3000	6250	15 gal/56.9 liter	6.4/.18	61 / 27.7	No
CWTF Twin APS*	23400.6008	120/240	26	2 @ 3000	6250	15 gal/56.9 liter	6.4/.18	61 / 27.7	No

*Airpots not included *Model has gourmet funnel.*
Brewing capacity: based upon incoming water temp of 60ºF (140ºF rise) per ½ gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: 3-wires plus ground service rated 120/240V, single phase, 60Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ⅜" (9.25 mm) male flare fitting.



Bunn-O-Matic Corporation of Canada - 280 Industrial Pkwy. S. Aurora, Ontario L4G 3T9 • 905-841-2866 • Fax 905-841-2775 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in inches. *Bunn Corporation owns all copyrights relating to materials in this publication. Please contact Bunn Corporation to request permission to reproduce any portion of this publication.*