

BUNN®

Powdered Autofill Ultra™ Frozen Beverage System with 2 Hoppers

ITEM#

PROJECT

DATE



Model ULTRA-2 PAF

Dimensions:
42"H x 16"W x 25"D
(106.7cm H x 40.6cm W x 63.5cm D)

Features

Ultra Frozen Beverage System

- Powdered autofill product hoppers refill product at a rate of 1.1 fluid oz./sec.
- Patented reversing auger design quickens freeze time and reduces air mixing.
- Very simple to program and run with touchpad display, which also guides cleaning and preventive maintenance.
- Enhanced "no-lube" design on faucets and seals which simplifies installation and cleaning.
- Refrigeration system internally monitored to ensure long lasting performance.
- Two large 2 gallon (7.57 litre) hoppers for optimum cooling & serving capacity.
- Full 3-year parts and labor warranty on electronics and 5-year parts warranty on compressor. See the product manual for additional details.
- Sanitation listed by NSF to Standard 18 (includes dairy & alcohol) and safety listed by ETL to UL Standard (UL 471) and CSA Standard (C22.2 No. 120).
- International electrical configurations available.
- LED backlighting for displays.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Conversion Kit

Kit converts hoppers on CDS-2 PAF machine to new ULTRA-2 PAF style hopper/faucet.

CDS-2 PAF Hopper Kit

Product No.: 28485.0046



Plastic hoppers pull out easily to refill powdered product.

Model

ULTRA-2 PAF

Agency Listing



7/10

D2

Dimensions & Specifications

Model	Product #	Volts	Amps	Capacity	Cu Ft.	Shipping Weight	Cord Attached
ULTRA-2 PAF (White/Stainless)	34000.0500	120	15	5 lbs. dry product	21.5 ft ³	177.6 lbs.	Yes*
ULTRA-2 PAF (Black/Stainless)	34000.0501	120	15	5 lbs. dry product	21.5 ft ³	177.6 lbs.	Yes*
ULTRA-2 PAF (All Black)	34000.0504	120	15	5 lbs. dry product	21.5 ft ³	177.6 lbs.	Yes*

*Power cord (NEMA 5-15P) 15 Amp-120V machine only.

Electrical: Model requires 2-wires plus ground service rated 120V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 1/4" male flare fitting.

