



a Standex company

ITEM: \_\_\_\_\_ PROJECT NAME: \_\_\_\_\_ DATE: \_\_\_\_\_

## HYBRID MERCHANDISER

**SERVICE HOT OVER  
SELF-SERVE REFRIGERATED**

MODEL  CH3628/RSS3SC  
 CH4828/RSS4SC  
 (2)CH3628/RSS6SC

**SELF-SERVE HOT OVER  
SELF-SERVE REFRIGERATED**

MODEL  CH3628SS/RSS3SC  
 CH4828SS/RSS4SC  
 (2)CH3628SS/RSS6SC



*Display more product and serve more customers with presentation and value in mind.  
Cases are available in lengths of 36", 48", and 72".*

### STANDARD FEATURES

#### Refrigerated Self-Serve Bottom Display

- Black laminated exterior. Other finishes available.
- Black trim. Silver optional.
- Black interior, glass ends.
- Horizontal top and front light.
- Two tiers black metal shelves.
- Cord and plug. (Not available on six foot unit.)

#### Service or Self-Serve Hot Top Display

- Two adjustable stainless steel heated shelves.
- Incandescent top and shelf lights.
- Sliding rear doors.
- Stainless steel deck.
- Black trim.
- Humidified air system on service model.
- Self-Serve has three hinged lift-up front doors.

# SERVICE HOT OVER SELF-SERVE REFRIGERATED MERCHANDISER

## OPTIONAL ACCESSORIES:


### For Top Display

- Reflective Ends
- Reflective Rear Doors


### For Self-Serve Refrigerated Base

- Energy Saving Night Curtain
- Silver Trim
- Special Base Finish
- Mirrored Interior Ends
- Security Night Cover
- Stainless Steel Steps in Lieu of Metal Shelves
- Reflective End Glass

## SERVICE HOT OVER SELF-SERVE REFRIGERATED



## SELF-SERVE HOT OVER SELF-SERVE REFRIGERATED



## SPECIFICATIONS:

Model	Dimensions L W H	Approx. Shipping Weight (lbs)	Self-Contained 120/60/1	Top Display
<input type="checkbox"/> CH3628/RSS3SC	36 1/4" x 39" x 69 3/4"	790	1/3 HP • 14.8 AMPS	8.4 AMPS
<input type="checkbox"/> CH4828/RSS4SC	48" x 39" x 69 3/4"	935	1/2 HP • 16.0 AMPS	11 AMPS
<input type="checkbox"/> (2)CH3628/RSS6SC	72" x 39" x 69 3/4"	1,400	3/4 HP • 16.0 + 10 AMPS	(2) 8.4 AMPS
<input type="checkbox"/> CH3628SS/RSS3SC	36 1/4" x 39" x 69 3/4"	790	1/3 HP • 14.8 AMPS	7 AMPS
<input type="checkbox"/> CH4828SS/RSS4SC	48" x 39" x 69 3/4"	935	1/2 HP • 16.0 AMPS	7.5 AMPS
<input type="checkbox"/> (2)CH3628SS/RSS6SC	72" x 39" x 69 3/4"	1,400	3/4 HP • 16.0 + 10 AMPS	(2) 7.0 AMPS

- Refrigerated cases are designed to operate in an environment of 75°F ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.
- On the six foot display a separate 120/60/1 15 AMP circuit is required for the condensate evaporator.



*The Signature of Quality*

**FEDERAL INDUSTRIES**  
A Standex Company

215 FEDERAL AVENUE, BELLEVILLE, WISCONSIN 53508-9201

PHONE: 800-356-4206

EMAIL: geninfo@federalind.com

FAX: 608-424-3234

WEBSITE: www.federalind.com

