



( 2 ), ( 3 ), ( 4 ), ( 5 ), ( 6 ) DOORS

**GRAB-N-GO CASES**

*MEDIUM TEMPERATURE  
HIGH VOLUME WITH FRONT DOORS  
FRONT AND REAR LOADING*

**MODELS**

**KGV - DL - ( 2, 3, 4, 5, 6 ) - S**



**SELF CONTAINED**

**404A REF - FORCED AIR REFRIGERATION**



Tel.: 514.737.9701 / Toll Free: 888.275.4538  
Fax: 514.342.3854 / Toll Free: 877.453.8832  
sales@mvpgroupcorp.com www.mvpgroupcorp.com

Abco Enterprises

# HIGH VOLUME GRAB-N-GO



# FRONT DOORS FRONT LOAD

| SELF CONTAINED | MODEL     | NO. OF DOORS | O.A LENGTH INCHES | CASE TEMP | ELECTRICAL        |                 |                   | WEIGHT |                              |
|----------------|-----------|--------------|-------------------|-----------|-------------------|-----------------|-------------------|--------|------------------------------|
|                |           |              |                   |           | COMPRESSOR        |                 |                   |        | LIGHTS AND FANS<br>115 VOLTS |
|                |           |              |                   |           | 115 VOLTS         |                 |                   |        |                              |
|                |           |              |                   |           | H.P               | F.L.A.          | L.R.A.            |        |                              |
| KGV-FD-2-S     | 2-23-1/2" | 51-1/2"      | 39/41 F           | 1/2       | 8.4               | 41              | 2.2               | 574    |                              |
| KGV-FD-3-S     | 3-23-1/2" | 75-3/8"      | 39/41 F           | 1/2       | 9.9               | 49              | 2.8               | 842    |                              |
| KGV-FD-4-S     | 4-23-1/2" | 99-3/8"      | 39/41 F           | (2) 1/2   | (2) 8.4           | (2) 41          | (2) 2.2           | 1048   |                              |
| KGV-FD-5-S     | 5-23-1/2" | 123-1/8"     | 39/41 F           | (2) 1/2   | (1) 8.4 + (1) 9.9 | (1) 41 + (1) 49 | (1) 2.2 + (1) 2.8 | 1184   |                              |
| KGV-FD-6-S     | 6-23-1/2" | 147"         | 39/41 F           | (2) 1/2   | (2) 9.9           | (2) 49          | (2) 2.8           | 1260   |                              |

THESE CASES ARE DESIGNED TO OPERATE USING R404A REFRIGERANT  
 B.T.U.'S CALCULATED AT +10° F EVAP AND 90° F AMBIENT  
 CASES ENGINEERED TO OPERATE AT 75° F AND 55% RH  
 FLOOR DRAINS REQUIRED

### STANDARD FEATURES

- INSULATION - HIGH DENSITY CFC FREE POLYURETHANE FOAM
- INTERIOR - PVC COATED STEEL-GRAY
- EXTERIOR - PVC COATED STEEL-SILVER
- ENDS-FOAMED -BLACK POLYSTYRENE
- CORD AND PLUG - ON 20 AMP OR LESS
- CASES ARE MULTIPLEXIBLE
- LED LIGHTING IN CANOPY AND UNDER ALL SHELVES
- HIGH PRESSURE SAFETY ALARM
- DEFROST AND TEMPERATURE REGULATED BY A DIGITAL CONTROLLER
- ADJUSTABLE SHELVES
- ADJUSTABLE FEET
- ETL LISTED TO UL471 AND SANITATION CLASSIFIED TO NSF7

### OPTIONAL FEATURES

- OTHER COLORS AVAILABLE
- STAINLESS STEEL EXTERIOR
- STAINLESS STEEL INTERIOR
- ADDITIONAL SHELVES
- PRICE TAG MOULDING

### WARRANTY

ONE YEAR PARTS AND LABOR WITH FOUR ADDITIONAL YEARS COMPRESSOR (PARTS ONLY)

