IS 8 - 12 - 16 X

manual sausage stuffers



- Manual sausage stuffers made completely of stainless steel
- Hardened steel gears sliding on ball bearings, piston rack sliding on heavy-duty teflon bushings to withstand the pressure of the hardest sausages
- 2-speed gear drive
- 3 nozzles 3/8", 3/4", 1" as standard
- Easy and fast breakdown for cleaning
- The vertical model IS 12 VX features a no-spillage lock pin to conveniently load the product without removing the cylinder

Features

Technical

- Complete stainless steel construction.
- Stainless steel 18/10 cylinder with no edge inside and no weld rests.
- · Hardened steel gears sliding on bearings.
- System of forward-backward feeding with two speeds.
- The piston valve allows excess air to escape and closes when the piston touches the meat.

Sanitary

· Can be completely disassembled for an easy and accurate cleaning







Funnel storage




Product loading without removing cylinder




Tilt-cylinder with no-spillage lock pin



IS 12 VX



0 V	4-	4.40900	04/01	4.00000	0.01 0.4
	lbs	inch.	Ø inch.	inch.	inch.
	Cylinder capacity	Cylinder length	Cylinder diameter	Piston stroke	Ø Serie exaust funnels



	Cylinder capac	Cylinder length	Cylinder diame	Piston stroke	Ø Serie exaust	А	В	С	D	E	F	Net weight	Shipping	Gross weight
	lbs	inch.	Ø inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	lbs.	inch.	lbs.
IS 8 X	17	149/16"	61/2"	169/16"	3/8" - 3/4" - 1"	77/8"	167/8"	26"	811/16"	-	-	41	28 ^{3/4} " x 10 ^{1/4} " x 9 ^{13/16} "	44
IS 16 X	35	1911/16"	77/8"	221/16"	3/8" - 3/4" - 1"	97/16"	225/8"	325/16"	913/16"	-	-	51	35 ^{1/16} " x 12 ^{3/16} " x 11"	54
IS 12 VX	25	1415/16"	77/8"	169/16"	3/8" - 3/4" - 1"	153/4"	71/2"	171/8"	913/16"	311/4"	2311/16"	52	35 ^{1/16} " x 12 ^{3/16} " x 11"	57

