



Sirman Spa
Viale dell'Industria 9/11
35010 PIEVE DI CURTAROLO (PD), Italy
Tel./Fax. +39 049 9698666 / +39 049 9698688
email: info@sirman.com



Sirman SaUsage Stuffers , model IS 15 Idra-Usa :

- Complete stainless steel construction to withstand heavy-duty application
- Easily removed lid, cylinder and piston for thorough cleaning and sanitation to ensure the highest levels of hygiene and safety
- IP 67 waterproof & dustproof protection switch, flow dial regulator
- Side-mounted foot switch for convenience of operation
- Automatic piston decompression and shut-off
- 3 nozzles - 3/8", 3/4", 1" - as standard

Features »

Technical

- The machine is completely made of stainless steel for durable long life.
- Silicone gaskets acts inside the cylinder for better seal and longer life of the gasket.
- Side mounted foot switch for more comfortable operation.
- Three stuffing nozzles included (3/8", 3/4", 1").

Safety

- Overcurrent and no volt release protection

Sanitary

- The machine can be completely disassembled for an easy and accurate cleaning.

Option

- Stainless steel nozzle lock ring
- Set of 4 stainless steel nozzles (Ø 1/2" - Ø 5/8" - Ø 13/16" - Ø 1 1/2")

Specifications

Motor: 3/4 Hp (520 W), fan cooled. **Electrical:** 220V AC, 60Hz, 1 phase. **Plug and Cord:** Attached, flexible, 3 wire (3PH+1G) SJT 12 AWG, 6'4" long cord. **Switch:** Stainless steel push-button keypad, IP 67 waterproof protection.



Easy and fast breakdown for cleaning



Easy access to inspect oil level and perform service



Optional stainless steel nozzles
Ø 1/2" - Ø 5/8" - Ø 13/16" - Ø 1 1/2"



Piston gasket




Side mounted foot switch



Optional stainless steel nozzle lock ring

Data sheet



Technical data

Model	IS 15 Idra
Power	watt 520 - 0,7 Hp
Cylinder capacity	lbs. 32
Cylinder length	19 1/2"
Cylinder diameter	7 7/8"
Piston stroke	16 15/16"
Min. forward speed	2' 11"
Backward speed	59"
Ø series exhaust funnels	35"
A	3/8" - 3/4" - 1"
B	19 5/16"
C	14 5/8"
D	27 9/16"
Net weight	47 1/4"
Shipping	lbs. 117
Gross weight	28 3/8" x 22 1/16" x 54 5/16"
HS-CODE	84385000